



Construction Products Regulation

Declaration of Performance

Identification Code: XFS4
Certificate Number: HS/FA/CH/CO/60XFS4

Serial number: None

Intended use: Concrete lintel intended for use in walls and partitions

Manufacturer: Naylor Concrete Products Ltd, Whaley Road, Barugh Green, Barnsley, South Yorkshire, S75 1HT

Assessment and verification of constancy of performance: System 3

Relevant harmonised standard: EN 845-2:2013 +A1:2016

Lucideon Ltd (Notified Body No.1289) carried out initial type testing to EN845-2:2013 under AVCP system 3 and issued test report Ref: UK24805 (QT-

73885/1/JB)/Ref. 1

Declared Performance

| XtraFire XFS4 | Lintel Length | | | | | | | | | | |
|---|---|-------|------|------|------|------|------|------|------|------|------|
| Essential Characteristics | 900 | 1100 | 1200 | 1500 | 1800 | 2100 | 2400 | 2700 | 3000 | 3300 | 3600 |
| Load bearing capacity (kNm-1) | 17.54 | 10.84 | 8.83 | 6.16 | 3.92 | 2.68 | 1.92 | 1.43 | 1.08 | 0.83 | 0.71 |
| Deflection at 1/3 of load capacity (mm) | 0.18 | | | 0.89 | | | | | 3.99 | | |
| Thermal resistance | Thermal conductivity λ _{10,dry, mat} (according to EN 1745) 1.52 W/m.K | | | | | | | | | | |
| Resistance to fire | R60 minutes | | | | | | | | | | |
| Durability of performance characteristics against corrosion | C2 - from table C3 EN 845-2:2013 (E) | | | | | | | | | | |
| Durability of performance characteristics against freeze/thaw cycle | Resistant | | | | | | | | | | |
| Water vapour permeability | NPD | | | | | | | | | | |
| Dangerous substances | None | | | | | | | | | | |

The performance of the product identified is in conformity with the declared performance above. This declaration of performance is issued under the sole responsibility of the manufacturer identified.